



## Toyota HiLux 4x4 Double Cabin GL 2.4TD

### Technical details:

Model code:	GUN25L-DTFLHV
Country of origin:	Thailand
Engine:	Turbo-diesel, 2,393 cc, 4-cyl. in-line 16V DOHC, EFI, intercooler, common rail, catalyst converter
Max output/Torque:	148 HP, 40.8 KgM
Transmission:	6-speed manual (floor), Part-time 4WD, Rear Diff. Lock
Tires and disc wheel:	225/70R17, steel wheels
Brakes front/rear:	Ventilated Disc/Rear Drum
Suspension:	Heavy duty. Front: Independent double wishbone, Rear: leaf spring with telescopic shock absorber
Seats:	6 seats (3+3) Fabric
Fuel tank capacity:	80L

### Standard Equipment:

- Power/tilt steering, Side impact beam
- ABS+EBD+BA+HAC+ATC+VSC+TSC
- Driver/Passenger Airbag + Knee (Driver)
- Bumper front and rear chrome, flat type
- Side stripe, Dust protection, Driver's seat vertical adjustable
- Fuel tank protector, Remote fuel lid opener
- Front bench seat, Rear seat for 3 persons tip-up type
- Power windows, Power door locks, Keyless entry
- Meter illumination control, Mud guards front and rear, Green laminated windshield
- Lockable glove box, Rear sliding window
- Chrome plated door mirrors, power with turn-signal, Chrome door handles
- Front seat belts 3PELRx2+2PNRx1, Rear seat belts 3PELRx2+2PNRx1
- Head rests front and rear 2+2, Adjustable seat belt anchor, front
- Tachometer, Digital clock, Multi reflector halogen head lamps
- Timing belt warning, Inner rear view mirror day/night
- Sun visors driver/passenger, Spare wheel anti-theft lock
- Wiper front adjustable intermittent
- AM/FM radio/CD/DVD w/2 speakers, USB, & AUX port and BT
- Antenna, short pole, Radiator grille chrome + silver
- Air-conditioner w/heater, Slide type rear window
- Multi info display TFT type, ECO/Power mode
- Urethane steering wheel with audio and BT controls
- Rear fog lamp, Tyre pressure monitoring system
  
- **Dimension & Weight**
- LWH : 5335 x 1815 x 1815 mm
- Deck dimensions LWH: 1520 x 1575 x 480 mm
- Wheelbase : 3090 mm
- Curb Weight : 1995 kg
- Gross Vehicle Weight : 2910 kgs
- Ground clearance: 286 mm
- Min. turning radius 6,4 M

NB! Specifications are subject to change without further notice and to be confirmed upon ordering