



Toyota Land Cruiser 200 GX-R8 SPL FLR A/T

Technical details:

Model Code	URJ202L-GNTAKV
Country of origin:	Japan
Engine	Petrol, 4,608cc, V8-cyl., DOHC, 32V, EFi, Dual VVTi
Max output/Torque	304 HP/5500 rpm, 44.76 KgM w/5500 rpm
Transmission	6 speed Automatic transmission, Full time 4WD, Torsen LSD, Differential lock
Tires and disc wheel	285/65R17 tires, 17" Steel wheels
Brakes front/rear	Ventilated Disc/Ventilated Disc
Suspension:	Front: Double wishbone, independent Rear: Coil springs, rigid
Seats	8 seats (2+3+3), Fabric
Fuel tank capacity	93 + 45 L

Standard Equipment:

- Power steering w/tilt function, Multi Terrain ABS+EBD+BA+VSC+ATRC+HAC+CRAWL CONTROL
- Side impact beam, Airbag driver/passenger
- Colour keyed bumper front and rear
- Mud guards front and rear, High mount stop lamp
- Windshield glass, green + top shade
- Colour keyed door mirrors, power with turn signal
- Colour keyed door handles, Console box with rear AC vent
- Leather/Wood steering wheel with audio control
- Fuel lid opener remote, Tachometer
- Front seat belts 3PELRx2, Rear seat belts 3PELRx6
- Digital clock, 2nd row 60/40 split foldable, reclining + slide
- Inner rear view mirror, Electrochromic, 3rd row 50/50 transverse
- Woodgrain panel, instrument panel, door trim
- Side steps, Rear window defogger
- Sun visors, 2, Vanity mirror, 2 with illumination
- Window wiper front and rear, intermittent
- Power windows, Power door lock
- Keyless entry, smart entry + push-start
- Radio AM/FM/CD/MP3//Bluetooth/6 speakers
- Glass integrated antenna, Illuminated entry system
- Air-conditioner front auto, rear manual w/heater
- Head lamps BI-LED/High Halogen, Rear Fog lamp
- Tire inflation pressure warning
- Engine immobilizer, Floor mats, Cruise control
- Rear luggage door, lift-up type, Spare wheel carrier floor type w/lock
- Radiator grille, Chrome/Silver, Combination meter
- Economy meter, Head lamp leveling function

- **Dimension & Weight**
- LWH : 5095 x 1980 x 1890 mm
- Wheelbase: 2850 mm
- Min. turning radius: 5,9 M
- Gross vehicle weight: 3350 kg
- Ground clearance: 230 mm

NB! Specifications are subject to change without further notice and to be confirmed upon ordering